## **EUROPEAN PATENT OFFICE**

## **Patent Abstracts of Japan**

**PUBLICATION NUMBER** 

60136169

**PUBLICATION DATE** 

19-07-85

APPLICATION DATE

26-12-83

APPLICATION NUMBER

58249073

APPLICANT: MITSUBISHI ELECTRIC CORP;

INVENTOR:

MIYOSHI HIDEAKI;

INT.CL.

H01M 4/88

TITLE

ELECTRODE RECOVERING METHOD OF PHOSPHORIC ACID TYPE FUEL CELL

ABSTRACT:

PURPOSE: To give water repellent property to a catalyst layer to recover performance of electrode for a cell by fluorinating the surface of carbon, carried with catalyst, of an electrode in which water repellent property of catalyst layer is deteriorated, to cover with a graphite fluoride film.

CONSTITUTION: An electrode for phosphoric acid type fuel cell, in which water repellent property of catalyst layer is deteriorated, is placed in an atmosphere of fluorine gas of 100-300°C. The surfasce of carbon carried with catalyst is fluorinated by adjusting F2 partial pressure and atmosphere and covered with graphite fluoride film to give water repellent ability to the catalyst layer. By this process, performance of the cell is recovered

without replacing with a new cell.

COPYRIGHT: (C)1985,JPO&Japio